

County Surveyor's Record, Douglas County, Oregon

14996

T. 25 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, and subdivisional lines, township 25 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys of that portion of the township pertaining to the following resurvey, is as follows:

The north boundary and subdivisional lines of the township, except the line between sections 6 and 7, and the line between sections 7 and 18, were surveyed by Robert Elder and Henry S. Gile, in 1853.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were re-established and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated June 1, 1972, for Group Number 769, Oregon.

The directions of the lines were determined by deflection angles from azimuths obtained by direct solar observations.

The geographic position of the southeast corner of section 3, as scaled from the Sutherlin, Oregon, quadrangle map, prepared by the United States Geological survey, in 1954, is as follows:

Latitude 43° 25.1' N. Longitude 123° 23.1' W.

The mean magnetic declination is 19° 21' E.

Dependent Resurvey of a Portion of the North Boundary,
T. 25 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1853 survey by Robert Elder
and Henry S. Gile, Deputy Surveyors)

From the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

*FO. OK 9/93
BY DOLAN, C.S. 63/97-3*

T 24 S R 6 W
S 34 | S 35
S 3 | S 2
T 25 S
1972

from which

A fir, 11 ins. diam., bears S. 29 1/2° E., 75 lks.
dist., mkd. T25S R6W S2 BT.