

County Surveyor's Record, Douglas County, Oregon

14997

Dependent Resurvey, Portion of North Boundary,
T. 25 S., R. 6 W., Willamette Meridian, Oregon.

CHAINS

A fir, 7 ins. diam., bears S. 41° W., 107 lks.
dist., mkd. T25S R6W S3 BT.

A fir, 12 ins. diam., bears N. 23 1/2° W., 247 lks.
dist., mkd. T24S R6W S34 BT.

From this point, the cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., bears S. 89° 54' E., 80.40 chs. dist., perpetuated and recorded by the Douglas County Surveyor, in 1923, subsequently perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron pipe, 3/4 in. diam., firmly set, extending 8 ins. above ground, with brass cap mkd.

T 24 S	S 36
S 35	S 36
S 2	S 1 R 6W
1962	

from which the remains of the original bearing trees

A black oak, 29 ins. diam., bears N. 73 3/4° E.,
279 lks. dist., with healed blaze.

A root hole, bears N. 65 1/4° W., 177 lks. dist., with
a down oak snag alongside, size indeterminate,
no marks visible.

and bearing trees mkd. by the County Surveyor, in 1923

A black oak, 11 ins. diam., bears N. 34° E., 19 1/2
lks. dist., with healed double blaze.

A white oak, 8 ins. diam., bears S. 29° E., 13 lks.
dist., with healed double blaze.

A fir, 17 ins. diam., bears S. 52° W., 33 lks.
dist., with healed double blaze,

A fir, 13 ins. diam., bears N. 41 1/2° W., 67 lks.
dist., with healed double blaze.

N. 89° 54' W., bet. secs. 3 and 34, marking and blazing
the true line.

Descend 35 ft. over SW. slope. through scattering timber
and undergrowth.

- .10 Wire fence, bears N. and S.
 - .70 Dirt road, 20 lks. wide, bears N. 40° W. and S. 20° E.
 - 2.25 Ravine, drains S. 10° W.; asc. 45 ft. over SE. slope.
 - 5.15 Spur, slopes S. 20° W.; desc. 80 ft. over W. slope.
 - 9.70 Ravine, drains S.; asc. 210 ft. over E. slope.
 - 20.10 Point for the E 1/16 sec. cor of sec. 3 and 34.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

E 1/16	S 34
	S 3
1972	

from which