

County Surveyor's Record, Douglas County, Oregon

14998

Dependent Resurvey, Portion of North Boundary,
T. 25 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A madrone, 5 ins. diam., bears N. 75 1/2° E., 63 lks.
dist. mkd. X BT on double blaze.

An oak, 7 ins. diam., bears S. 5° W., 156 lks.
dist., mkd. E 1/16 S3 BT.

The corner point is located on a spur, slopes S. 30° W.
Descend 255 ft. over NW. slope.

34.05 Ravine, drains S. 35° W.; asc. 45 ft. over SE. slope.

36.05 Spur, slopes S. 10° W.; desc. 25 ft. over SW. slope.

39.65 Wire fence, bears N. and S.

40.20 Point for the 1/4 sec. cor. of secs. 3 and 34, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

*FND. OK
6-94 BT DeGroot
M119-3A*

T 24 SR 6 W
1/4 S 34
S 3
T 25 S
1972

from which

A madrone, 7 ins. diam., bears N. 37 1/2° E., 21 lks.
dist., mkd. 1/4 S34 BT.

An oak, 10 ins. diam., bears S. 29° E., 151 lks.
dist., mkd. 1/4 S3 BT.

Descend 470 ft. over SW. slope.

41.55 Wire fence, bears N. 65° E. and S. 65° W.

52.90 Dirt road, 25 lks. wide, bears N. and S.

58.30 Center line of Oregon State Highway No. 138, 40 lks.
wide, paved, bears N. 30° W. and S. 30° E.

63.45 Creek, 10 lks. wide, course S.; asc. 175 ft. over SE.
slope.

66.00 Dirt road, 15 lks. wide, bears N. and S.

75.40 Top of ascent, slopes S.; desc. 25 ft. over SW. slope.

80.40 The cor. of secs. 3, 4, 33, and 34, perpetuated and
recorded by G. G. Stewart, Deputy County Surveyor, in
1922, when original corner evidence was still existent,
monumented with an iron pipe, 1 1/2 ins. diam., firmly set,
extending 8 ins. above ground, from which bearing trees
mkd. by Stewart:

A decayed fir stump, size indeterminate, bears
S. 48° W., 71 lks. dist., with scribe marks
4 BT visible on open blaze.

A fir, 30 ins. diam., bears N. 16° W., 15 lks.
dist., with healed blaze.