

# County Surveyor's Record, Douglas County, Oregon

14999

Dependent Resurvey, Portion of North Boundary,  
T. 25 S., R. 6 W., Willamette Meridian, Oregon.

CHAINS

and bearing trees mkd. by the County Surveyor, in 1962

A fir, 21 ins. diam., bears N. 28° E., 54 1/2 lks.  
dist., with healed double blaze.

A white oak, 9 ins. diam., bears S. 32° E., 14 lks.  
dist., with healed blaze.

A white oak, 13 ins. diam., bears S. 74° W., 98  
lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, directly atop iron pipe, with brass cap mkd.

FO. OK G-94  
BT DeGroot M119-3A

T 24 S R 6 W  
S 33 | S 34  
S 4 | S 3  
T 25 S  
1972

The corner point is located in a wire fence, extending  
N. and S.

Land, mountainous.

Soil, rocky clay.

Timber, white oak, black oak, madrone, fir, and cedar;  
undergrowth, poison oak, hazel, and blackberry.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 25 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1853 survey by Robert Elder  
and Henry S. Gile, Deputy Surveyors)

From the cor. of secs. 2, 3, 10, and 11, perpetuated and  
recorded by G. G. Stewart, Deputy County Surveyor, in  
1922, and subsequently perpetuated and recorded by Milo  
E. Godfrey, Deputy County Surveyor, in 1962, monumented  
with an iron pipe, 3/4 in. diam., firmly set, extending  
8 ins. above ground, with brass cap mkd.

T 25 S  
S 3 | S 2  
S 10 | S 11  
R 6 W  
1962

from which the remains of the original bearing tree

A white oak, 21 ins. diam., bears S. 64° E., 124  
lks. dist., with healed blaze.

and bearing trees mkd. by Stewart

A white oak, 22 ins. diam., bears N. 35 1/2° E., 177  
lks. dist., with healed blaze.

A pine, 23 ins. diam., bears S. 13° W., 208 lks.  
dist., with healed blaze.

and bearing trees mkd. by Godfrey