

County Surveyor's Record, Douglas County, Oregon

15000

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A white oak, 9 ins. diam., bears S. 43° E., 29 lks. dist., with healed blaze.

A madrone, 20 ins. diam., bears N. 42° W., 247 lks. dist., with scribe marks T25S R6W S3 CS BT visible on open blaze.

The corner point is located in a wire fence, extending N. and S.

N. 0° 05' E., bet. secs. 2 and 3, marking and blazing the true line.

Ascend 185 ft. over broken SE. slope, through moderate timber and undergrowth.

19.85 From this point, a local point bears West, .150 chs. dist., monumented with an iron pipe, 3/4 in. diam., firmly set, extending 6 ins. above ground. Also, wire fence bears E. and W.

19.995 Point for the S 1/16 sec. cor. of secs. 2 and 3.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 3 | S 2
1972

from which

A fir, 15 ins. diam., bears N. 78 3/4° E., 91 lks. dist., mkd. S 1/16 S2 BT.

A fir, 28 ins. diam., bears N. 14 1/2° W., 109 lks. dist., mkd. S 1/16 S3 BT.

Ascend 140 ft. over SE. slope.

33.00 Dirt road, 20 lks. wide, at top of ascent, slopes S. 30° W., bears N. 25° E. and S. 25° W.; desc. 10 ft. over NW. slope.

39.99 The 1/4 sec. cor. of secs. 2 and 3, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, when original corner evidence was still existent, subsequently perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron pipe 3/4 in. diam., firmly set, extending 8 ins. above ground, with brass cap mkd.

*FD. OK 6-70
BT DeGroot M119-34*

T 25 S
1/4 S 3 | S 2
R 6 W
1962

from which bearing trees mkd. by Stewart

A root hole, bears N. 63° W., 89 lks. dist., with remains of a fir alongside, size indeterminate, no marks visible.

A burned fir stump, bears S. 59° W., 24 lks. dist., with axe marks visible on opened blaze.

and trees mkd. by Godfrey, in 1962