

County Surveyor's Record, Douglas County, Oregon

15002

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	wide, paved, bears N. 50° W. and S. 50° E.
6.20	Wire fence, bears N. 50° W. and S. 50° E., enter pasture.
12.00	Enter scattering timber, edge bears N. 20° W. and S. 20° E.
12.10	Creek, 10 lks. wide, course S. 20° E.; asc, 175 ft. over NE. slope.
19.985	Point for the E 1/16 sec. cor. of secs. 3 and 10, Set an iron post, 28 ins. long, 2 1/2 ins diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $E \frac{1}{16} \frac{S \ 3}{S \ 10}$ 1972 </div> from which A fir, 12 ins. diam., bears N. 86° E., 90 1/2 lks. dist., mkd. E 1/16 S3 BT. A fir, 7 ins. diam., bears S. 20 1/2° W., 85 lks. dist., mkd. X BT. Ascend 255 ft. over NE. slope.
32.50	Spur, slopes N.; desc. 30 ft. over broken NW. slope.
39.62	Wire fence, bears N. and S.
39.97	Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $T \ 25 \ S \ R \ 6 \ W$ $1/4 \ \frac{S \ 3}{S \ 10}$ 1972 </div> from which A fir, 12 ins. diam., bears N. 54 1/2° W., 126 1/2 lks. dist., mkd. 1/4 S3 BT. An oak, 7 ins. diam., bears S. 67 1/2° W., 99 lks. dist., mkd. 1/4 S10 BT. The corner point is located .45 chs. North of wire fence, extending generally E. and W. Ascend 10 ft. over broken NE. slope, along a wire fence.
41.05	Spur, slopes N.; desc. 230 ft. over NW. slope.
50.30	Enter heavy timber and moderate undergrowth, edge bears N. and S.
56.00	Ravine, drains. N. 20° E.; asc. 20 ft. over NE. slope.
57.80	Spur, slopes N.; desc. 40 ft. over NW. slope.
59.995	Point for the W 1/16 sec. cor. of secs. 3 and 10.

FO. OK 6/94
B1 DEGR00T M119-2A