

County Surveyor's Record, Douglas County, Oregon

15003

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 3}{S\ 10}$
1972

From which

A fir, 9 ins. diam., bears N. 1/2° E., 33 lks. dist., mkd. W 1/16 S3 BT.

A fir, 8 ins. diam., bears South, 42 1/2 lks. dist., mkd. W 1/16 S10 BT.

The corner point is located .02 chs. North of wire fence extending generally E. and W.

Descend 45 ft. over NW. slope.

62.35 Wire fence, bears NW. and SE.

62.65 Ravine, drains N. 30° E.; asc. 140 ft. over SE. slope.

65.65 Wire fence, bears N. 65° W. and S. 65° E.

73.30 Top of ascent, slopes N.; desc. 15 ft. along N. slope.

75.25 Ravine, drains. N.; asc. 35 ft. over broken NE. slope.

79.94 The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, when original corner evidence was still existent, subsequently perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron pipe, 3/4 in. diam., firmly set, extending 4 ins. above ground, with brass cap mkd.

T 25 S
S 4 | S 3
S 9 | S 10
R 6 W
1962

from which bearing trees mkd. by Stewart, in 1922

A fir, 16 ins. diam., bears N. 63° E., 22 lks. dist., with healed blaze.

A fir snag, 48 ins. diam., bears S. 58° W., 40 lks. dist., with healed blaze.

A decayed fir stump, 24 ins. diam., bears N. 19° W., 40 lks. dist., with scribe marks BT visible on decayed blaze.

and trees mkd. by Godfrey, 1962

A cedar, 15 ins. diam., bears S. 32° E., 105 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears S. 10° W., 78 lks. dist., with healed blaze.

A cedar, 19 ins. diam., bears S. 75° W., 144 lks. dist., with healed blaze.