

County Surveyor's Record, Douglas County, Oregon

15004

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The corner point is located .02 chs. North of a wire fence extending N. 55° E. and S. 55° W.

Land, mountainous.

Soil, rocky clay.

Timber, fir, oak, cedar, maple, madrone, and cascara; undergrowth, poison oak, hazel, wild strawberry, blackberry, and fern.

N. 0° 15' W., bet. secs 3 and 4.

Ascend 10 ft. over NE. slope, through moderate timber and undergrowth.

.12 Wire fence, bears N. 80° W. and S. 80° E.

1.20 Spur, slopes N. 65° E.; desc. 165 ft. over NE. slope.

6.65 Creek, 3 lks. wide, course S. 70° E.; asc. 300 ft. over S. slope.

19.90 Wire fence, bears E. and W.

20.04 Point for the S. 1/16 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 4 | S 3
1972

from which

A fir, 12 ins. diam., bears N. 82 1/2° E., 83 lks. dist., mkd. S 1/16 S3 BT.

A fir, 7 ins. diam., bears N. 40° W., 54 lks. dist., mkd. S 1/16 S4 BT.

Ascend 115 ft. over SW. slope.

32.40 Spur, slopes E.; desc. 50 ft. over NE. slope.

40.08 The 1/4 sec. cor. of secs. 3 and 4, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, subsequently perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron pipe, 3/4 ins. diam., firmly set, extending 4 ins. above ground, with brass cap mkd.

*FOOK
6/94 BY DeGroot
M119-3A*

T 25 S
S | S
1/4 4 | 3
R 6 W
1972

from which the remains of the original bearing tree

A fir snag, 16 ins. diam., bears S. 11° E., 27 lks. dist., no marks visible.

and trees mkd. by Stewart, in 1922

A root hole, bears S. 10° E., 18 lks. dist., with a down fir alongside, 10 ins. diam., with axe marks visible on burned blaze.