

County Surveyor's Record, Douglas County, Oregon

15007

T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 20 south, range 9 west, Willamette Meridian, Oregon.

The history of surveys in that portion of the township pertaining to this resurvey is as follows:

A portion of the subdivisional lines was surveyed by William Thiel, in 1877.

A portion of the subdivisional lines was surveyed by William Thiel, in 1891.

A portion of the subdivisional lines was resurveyed by Thomas A. Tillman and Joseph S. Gawron, in 1953-54.

Certain original corner points within the township were remonumented without survey by William W. Glenn and James E. Jelley, in 1967.

Preliminary to the resurvey, lines of the original survey were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 21, 1972, for Group 777, Oregon.

The directions of the lines were determined by the solar transit method and by deflection angles turned from azimuths obtained by direct solar observations.

The geographic position of the 1/4 section corner of sections 32 and 33, as scaled from the Goodwin Peake, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1956, is as follows:

Latitude 43° 47.4' N. Longitude 123° 47.3' W.

The mean magnetic declination is 20° 30' E.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 W., R. 9 W., Willamette Meridian, Oregon

(Restoring the 1877 survey by William Thiel,
U. S. Deputy Surveyor, and
the 1953-54 resurvey by Thomas A. Tillman and
Joseph S. Gawron, Cadastral Engineers)

Beginning at the 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 in. diam., firmly set, protruding 1 in. above ground, with brass cap mkd.

Field OK by EIM STAD
Aug. 1981 M 89-13

1/4
S 32 | S 33
1953

from which the remains of the original bearing trees