

County Surveyor's Record, Douglas County, Oregon

15009

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

33.40 Left bank of Smith River, bears N. 30° W., and S. 30° E.; thence across river.

37.90 Right bank of the Smith River, bears N. 30° W. and S. 30° E.; asc. 30 ft. over nearly level ground.

40.34 Center line, Smith River Road, asphalt surfaced, 30 lks. wide, bears N. 30° W. and S. 30° E.

40.44 The cor. of secs. 28, 29, 32, and 33, determined at record bearing and distance from the remains of the original bearing trees:

A fir stump, 45 ins. diam., bears N. 25 3/4° E., 126 lks. dist., with healed blaze.

and bearing trees and reference monuments mkd. by Tillman and Gawron

A fir, 47 ins. diam., bears N. 44 1/2° E., 122 lks. dist., with healed blaze.

An iron post, 2 ins. diam., firmly set, protruding 6 ins. above ground, bears N. 45° E., 90 lks. dist., with brass cap mkd. T20S R9W S28 RM 1953 and an arrow pointing to the corner, alongside of which a steel fence post, firmly set, protruding 4 ft. above ground.

A fir, 50 ins. diam., bears S. 73 1/2° E., 106 lks. dist., with healed blaze.

An iron post, 2 ins. diam., firmly set, protruding 8 ins. above ground, bears S. 45° W., 90 lks. dist., with brass cap mkd. T20S R9W S32 RM 1953 and an arrow pointing to the corner.

A fir, 34 ins. diam., bears S. 50° W., 83 lks. dist., with healed blaze.

A fir, 37 ins. diam., bears N. 7° W., 175 lks. dist., with healed blaze. (Record, N. 13 3/4° W.)

and a bearing tree of which I have no record

A fir, 45 ins. diam., bears N. 84 3/4° E., 129 lks. dist., with healed blaze.

At the corner point

Drive a concrete nail, 1 1/2 ins. long, 1/4 ins. diam., head, into asphalt roadway, with head flush with surface.

Land, mountainous.
Soil, rocky clay, snady clay loam.
Timber, fir, hemlock, cedar, alder, maple, yew, and dogwood; undergrowth, fern, vine maple, poison oak, rhododendron, salal, huckleberry, salmonberry, and haze.

A FD. OK
 8/8/81
 W. SIMSTAD
 M89-13

From the 1/4 sec. cor. of secs. 31 and 32, monumented with an iron post, 1 in. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

1/4
S 31 | S32
1953

Fwd OK. by EIMSTAD
 Aug. 1981 M 89-13
 2/92
 REPT. WARD
 M114-48