

County Surveyor's Record, Douglas County, Oregon

15010

Dependent Resurvey, Portion of Subdivisional Lines,

CHAINS

T. 20 S., R. 9 W., Willamette Meridian, Oregon

from which bearing trees mkd. by Tillman and Gawron

A fir, 18 ins. diam., bears N. 34° E., 9 lks. dist., with healed blaze.

A fir, 32 in.s diam., bears N. 58 1/2° W., 23 lks. dist., with healed blaze.

N. 0° 18' E., bet. secs. 31 and 32.

Ascend 40 ft. over S. slope, through heavy timber and dense undergrowth.

- 1.15 Spur, slopes SW., asc. 110 ft. along W. slope.
- 8.40 Spur, slopes SW.; desc. 85 ft. over NW. slope.
- 9.50 Head of ravine, drains. S. 75° W.; asc. 190 ft. over broken SW. slope.
- 14.75 Top of ascent, slopes W.; desc. 280 ft. over NW. slope.
- 20.15 Creek, 2 lks. wide, course N. 70° W.; asc. 10 ft. over SW. slope.
- 20.94 Point for the N 1/16 sec. cor. of secs. 31 and 32.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 9 W
N 1/16
S 31 | S 32
1972

from which

A fir, 18 ins. diam., bears N. 54° E., 61 lks. dist., mkd. N 1/16 S32 BT.

An alder, 33 ins. diam., bears S. 20° W., 24 1/2 lks. dist., mkd. N 1/16 S31 BT on bark.

Ascend 20 ft. over SW. slope.

- 21.75 Top of ascent, slopes S. 70° W.; desc. 20 ft. over NW. slope.
- 23.30 Dry creek, drains S. 65° W.; asc. 25 ft. over SW slope.
- 24.40 spur, slopes S. 75° W.; desc. 320 ft. over broken NW. slope.
- 36.25 Creek, 4 lks. wide, course W.; asc. 40 ft. over S. slope.
- 41.88 The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.

T 20 S R 9 W
S 30 | S 29
S 31 | S 32
1953

*FD. OK 8/81
W. EIMSFAD
M 89-13*

from which the remains of the original bearing trees