

County Surveyor's Record, Douglas County, Oregon

15011

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S. R 9 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 50 ins. diam., bears N. 22 1/2° E.,
34 1/2 lks. dist., with scribe marks R9W visible on
open blaze.

A sawed fir stump, 54 ins. diam., bears S. 63 1/2° E.,
60 lks. dist., with healed blaze.

A sawed fir stump, 50 ins. diam., bears S. 36° W.,
16 lks. dist., with reverse scribe marks BT
visible on overgrowth.

and bearing trees mkd. by Tillman and Gawron

A fir, 28 ins. diam., bears N. 23 3/4° E., 56 lks.
dist., with healed blaze.

A hemlock, 30 ins. diam., bears S. 78° E., 65 lks.
dist., with healed blaze.

A sawed fir stump, 26 ins. diam., bears S. 59 1/2° W.,
63 lks. dist., with healed blaze.

A sawed fir stump, 24 ins. diam., bears N. 42 1/4° W.,
54 lks. dist., with healed blaze.

and new bearing trees

A cedar, 15 ins. diam., bears S. 62° W., 57 1/2 lks.
dist., mkd. T20S R9W S31 BT.

A fir, 13 ins. diam., bears N. 38 1/2° W., 57 lks.
dist., mkd. T20S R9W S30 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, alder, and maple; under-
growth, vine maple fern, salmonberry, hazel, huckle-
berry, arrowwood, and salal.

From the cor. of secs. 28, 29, 32, and 33.

N. 86° 50' W., bet. secs. 29 and 32.

Descend 40 ft. over nearly level ground, through no
timber or undergrowth.

.10 Center line, Smith River Road, asphalt surfaced, 30 lks.
wide, bears N. 30° W. and S. 30° E.

1.65 Right bank of Smith River, bears N. 30° W. and S. 30° E.;
thence across river.

4.60 Left bank of Smith River, bears N. 30° W. and S. 30° E.;
asc. 190 ft. over E. slope, through heavy timber and
dense undergrowth.

9.10 Top of ascent, slopes NW.; desc. 100 ft. over W. slope.

13.20 Creek, 4 lks. wide, course N. 60° W.; desc. 20 ft. over
W. slope.

18.07 Point for the E 1/16 sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.