

# County Surveyor's Record, Douglas County, Oregon

15012

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 9 W., Willamette Meridian, Oregon.

CHAINS

T 20 S R 9 W  
E 1/16  $\frac{S\ 29}{S\ 32}$   
1972

from which

A fir, 28 ins. diam., bears N. 79 3/4° E., 84  
lks. dist., mkd. E 1/16 S29 BT.

A fir, 43 ins. diam., bears S. 87 1/4° E., 133 lks.  
dist., mkd. E 1/16 S32 BT.

Descend 15 ft. over W. slope.

18.60 Creek, 5 lks. wide, course N.; asc. 35 ft. over NE.  
slope.

22.70 Creek, 2 lks. wide, course N; asc. 110 ft. over NE.  
slope.

33.70 Spur, slopes N.; desc. 40 ft. over NW. slope.

35.45 Ravine, course NE.; asc. 15 ft. over E. slope.

36.14 The 1/4 sec. cor. of secs. 29 and 32, monumented with an  
iron post, 1 in. diam., firmly set, in a mound of stone,  
3 ft. base, to top, with brass cap mkd.

*Find. OK by EIMSTAD  
Aug. 1980 M 89-13*

1/4  $\frac{S\ 29}{S\ 32}$   
1953

from which the original bearing trees

A fir, 55 ins. diam., bears N. 23° W., 60 lks.  
dist., with healed blaze.

A maple, 30 ins. diam., bears N. 89° W., 60 lks.  
dist., with healed blaze. (Record, S. 89° W.)

and bearing trees mkd. by Tillman and Gawron

A maple, 14 ins. diam., bears N. 31 1/2° W., 47 lks.  
dist., with healed blaze.

An alder stump, 23 ins. diam., bears S. 32° E.,  
51 lks. dist., with healed blaze.

N. 89° 47' W., beginning new measurement.

Ascend 70 ft. over NE. slope.

1.80 Spur, slopes NE.; desc. 10 ft. over W. slope.

3.40 Ravine, drains N. 40° E.; asc. 315 ft. over E. slope.

9.45 Ridge, bears N. and S.; desc. 120 ft. over NW. slope.

12.20 Ravine, drains N. 25° W.; asc. 110 ft. over NE slope.

14.00 Spur, slopes N. 20° W.; desc. 370 ft. over NW. slope.

20.79 Point for the W 1/16 sec. cor. of secs. 29 and 32.