

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy.
T. 21 S., R. 4 W., Willamette Meridian, Oregon

15016

CHAINS

A sawed cedar stump, 30 ins. diam., bears S. 10° E., 96 lks. dist., with axe marks visible on double blaze.

A sawed fir stump, 20 ins. diam., bears S. 88° W., 137 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S	FD OK PER GUILLE
R 5 W R 4 W	NOV. 1986, M103-9
S 12 S 7	FD. OK 12/91
S 13 S 18	D. PEEL M114-41
1971	

from which new bearing trees

A fir, 15 ins. diam., bears N. 69° E., 76 lks. dist., mkd. T21S R4W S7 BT.

A fir, 21 ins. diam., bears S. 84° E., 69 lks. dist., mkd. T21S R4W S18 BT.

A fir, 6 ins. diam., bears S. 60° W., 270 lks. dist., mkd. T21S R5W S13 BT.

A fir, 6 ins. diam., bears N. 36° W., 53 lks. dist., mkd. T21S R5W S12 BT.

Deposit cedar post alongside iron post.

N. 0° 31' E., bet. secs. 7 and 12, marking and blazing the true line.

Descend 10 ft. over N. slope, through moderate timber and dense undergrowth.

.90 Pheasant Creek, 5 lks. wide, course S. 20° E.; asc. 15 ft. over SE slope.

3.80 Same creek, 5 lks. wide, course W.; asc. 285 ft. over SE. slope.

11.05 Gravelled road, 30 lks. wide, bears N. 30° E. and S. 30° W.

21.00 Corner of fences, extending N. and E.

32.00 Top of ascent, slopes SE.; desc. 35 ft. over NE. slope.

37.55 Ravine, drains E.; asc. 10 ft. over SE. slope.

40.16 The 1/4 sec. cor. of secs. 7 and 12, perpetuated by person (s) unknown, monumented with an iron pipe, 3/4 ins. diam., firmly set, protruding 12 ins. above ground, from which the remains of the original bearing trees:

A root hole and fir roots, bears S. 43° E., 33 lks. dist.

A decayed fir stump, size indeterminate, bears S. 52° W., 18 lks. dist., no marks visible.

and a bearing tree of no record.