

# County Surveyor's Record, Douglas County, Oregon

15017

Dependent Resurvey, Portion of W. Bdy.,  
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 48 ins. diam., bears N. 15° E.,  
43 lks. dist., with scribe marks 1/4 S7 BT visible  
on weathered bark blaze.

At the corner point

Set an ironpost, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

1/4  
S 12 | S 7  
|  
T 21 S  
R 5 W R 4 W  
1971

from which new bearing trees

A fir, 10 ins. diam., bears N. 56° E., 29 lks.  
dist., mkd. 1/4 S7 BT.

A fir, 9 ins. diam., bears S. 24° W., 20 lks.  
dist., mkd. 1/4 S12 BT.

Deposit iron pipe alongside the iron post.

N. 0° 04' W., beginning new measurement.

Ascend 10 ft. over SE. slope.

- 1.20 Top of ascent, slopes SE.; desc. 165 ft. over NE slope.
- 14.30 Creek, 3 lks. wide, course S. 70° E.; asc. 195 ft. over S. Slope.
- 25.25 Spur, slopes SE.; desc. 15 ft. over NW. slope.
- 25.25 Ravine, drains S. 60° W.; asc. 205 ft. over SW. slope.
- 39.88 The cor. of secs. 1, 6, 7, and 12, perpetuated and recorded  
by Milo Godfrey, Deputy County Surveyor, in 1961,  
monumented with an iron post, 1 1/2 ins. diam., firmly set,  
protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S  
S 1 | S 6  
S 12 | S 7  
1961

from which the remains of the original bearing trees

A root hole, bears N. 43° E., 425 ft. dist., with  
a down sawed fir stump alongside, 36 ins. diam.,  
no marks visible.

A sawed fir stump, 44 ins. diam., bears N. 84 1/2° W.,  
135 lks. dist., with axe marks visible on bark.

and bearing trees mkd. by Godfrey

A fir, 13 ins. diam., bears N. 58 1/2° E., 82 lks.  
dist., with healed blaze.

A chinquapin, 8 ins. diam., bears S. 61° E., 40 lks.  
dist., with healed blaze.