

# County Surveyor's Record, Douglas County, Oregon.

**15019**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
11.90	Centerline of south bound lanes of Interstate Route 5, concrete surfaced, 60 lks. wide, bears same.
14.90	Centerline of Southern Pacific railroad tracks. 10 lks. wide, bears same.
16.05	Wire fence, bears same.
17.55	Pass Creek, 10 lks. wide, course S. 40° W.; asc. 10 ft. over nearly level ground.
20.025	Point for the S 1/16 sec. cor. of secs. 16 and 17.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 29 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     S 1/16                      S 17   S 16                      1972                 </div> No bearing trees available within limits.  <div style="text-align: center;">                     Set a steel fence post, 5 ft. long, 3 ft. in the ground alongside iron post.                 </div> Ascend 210 ft. over SE. slope.
31.65	Spur, slopes S. 40° E.; desc. 70 ft. over NE. slope.
36.75	Creek, 1 lk wide, course S. 30° E.; asc. 120 ft. over S. slope.
40.05	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     T 21 S R 4 W                      1/4                      S 17   S 16                      1972                 </div> from which  <div style="text-align: center;">                     A fir, 13 ins. diam., bears N. 25° E., 57 lks. dist., mkd. 1/4 S16 BT.                       A fir, 10 ins. diam., bears N. 15° W., 88 lks. dist., mkd. 1/4 S17 BT.                 </div> Ascend 70 ft. over S. slope.
45.50	Spur, slopes S. 40° E.; desc. 125 ft. over NE. slope.
49.50	Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
54.15	Dirt road, 15 lks. wide, bears S. 80° E. and N. 80° W.
57.95	Creek, 1 lk. wide, course N. 40° E.; asc. 50 ft. over broken SE. slope.
60.00	Wire fence, bears E. and W.
80.10	Point for the cor. of secs. 8, 9, 16, 17, at proportionate distance; there is no remaining evidence of the original corner.