

County Surveyor's Record, Douglas County, Oregon

15021

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by Springer

A sawed fir stump, 46 ins. diam., bears S. 57° E.,
106 lks. dist., with scribe mark X visible on
opened blaze.

and bearing trees mkd. by Tracy

A fir, 15 ins. diam., bears S. 26° E., 46 lks.
dist., with healed blaze.

A chingquapin, 9 ins. diam., bears West, 5 lks.
dist., with scribe marks 1/4 S8 CS BT visible on
partially healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 21 S R 4 W
1/4
S 8 | S 9
1972

Deposit iron pipe alongside the iron post.

Also from this same point, the 1/4 sec. cor. of secs. 8
and 17, bears N. 88° 23' W., 39.52 chs. dist., perpetuated
by James W. Byron, Deputy County Surveyor, in 1969,
monumented with an iron post, 2 ins. diam., firmly set,
protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1/4 T 21 S
S 8
S 17
R 4 W
1969

from which the remains of the original bearing trees

A fir stump, 48 ins. diam., bears S. 74° W.,
126 lks. dist., with scribe marks BT visible on
opened blaze.

and bearing trees mkd. by Byron

A fir, 22 ins. diam., bears N. 64° E., 43 lks.
dist., with healed double blaze.

A fir, 15 ins. diam., bears S. 29° W., 51 lks.
dist., with healed double blaze.

Land, rolling hills.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, alder, madrone, chinquapin,
maple, and yew; undergrowth, vine maple, hazel, fern,
salal, rhododendron, Oregon grape, and poison oak.

From the cor. of secs. 16, 17, 20, and 21.

N. 89° 43' W., bet. secs. 17 and 20.

Descend 90 ft. over SW. slope, through heavy timber and
light undergrowth.