

# County Surveyor's Record, Douglas County, Oregon

15024

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 21 S  
S 7 | S 8  
S 18 | S 17  
R 4 W  
1969

from which the remains of the original bearing tree

A fir, 50 ins. diam., bears S. 20° W., 19 lks. dist., no marks visible on opened blaze.

and a bearing tree mkd. by Springer

A sawed fir stump, 54 ins. diam, bears S. 67 1/2° E., 96 lks. dist., no marks visible.

and bearing trees mkd. by Tracey

A fir, 11 ins. diam., bears N. 43° E., 32 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 34° E., 27 lks. dist. with healed blaze.

A fir, 8 ins. diam., bears S. 85° W., 12 lks. dist., with healed blaze.

A fir, 9 ins. diam., bears N. 74° W., 15 lks. dist., with healed blaze.

S. 89° 36' W., bet. secs. 7 and 18.

Ascend 150 ft. over E. slope, through heavy timber and light undergrowth.

12.35 Top of ascent, slopes S.; desc. 170 ft. over SW. slope.

28.40 Ravine, drains S.; asc. 135 ft. over E. slope.

40.10 Point for the 14/ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4 S 7  
S 18  
T 21 S R 4 W  
1971

FD OK PER GUILLE  
NOV 1986, M 103-9

FD OK DEC. 1991  
D. PEEL M 114-41

from which

A fir, 8 ins. diam., bears N. 15° E., 49 lks. dist., mkd. 1/4 S7 BT.

A fir, 10 ins. diam., bears S. 21° W., 39 lks. dist., mkd. 1/4 S18 BT.

Ascend 5 ft. over E. slope.

40.95 Top of ascent, slopes S.; desc. 130 ft. over W. slope.