

County Surveyor's Record, Douglas County, Oregon

15025

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS													
48.15	Ravine, drains S.; asc. 5 ft. over nearly level ground.												
52.95	Top of ascent, slopes S.; desc. 25 ft. over SW. slope.												
55.35	Ravine, drains S.; asc. 70 ft. over SE. slope.												
60.15	Point for the W 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 10px;">W 1/16</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 7</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">S 18</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">1971</td> </tr> </table>	W 1/16	S 7			S 18				1971			
W 1/16	S 7												
	S 18												
		1971											
	<i>FL. 6/30 BLM</i> <i>ADMIN. SURVEY see</i> <i>"GIS" FILE</i>												
	from which												
	A fir, 5 ins. diam., bears N. 13° E., 33 lks. dist., mkd. W 1/16 S7 BT.												
	A fir, 20 ins. diam., bears S. 57° E., 68 lks. dist., mkd. W 1/16 S18 BT.												
61.95	Ridge, bears N. and S.; desc. 420 ft. over W. slope.												
80.20	Pheasant Creek, 3 lks. wide, course S.; asc. 5 ft. over E. slope.												
80.55	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the tp., hereinbefore described. Land, mountainous. Soil, rocky clay loam. Timber, fir, cedar, hemlock, maple, alder, madrone, and chinquapin; undergrowth, hazel, fern, salal, vine maple, and poison oak.												
	From the cor. of secs. 7, 8, 17, and 18. N. 0° 11' W., bet. secs. 7 and 8. Ascend 185 ft. over SE. slope, through scattering timber and dense undergrowth.												
40.57	The 1/4 sec. cor. of secs. 7 and 8, perpetuated by C. W. Springer, Deputy County Surveyor, in 1923, subsequently perpetuated by Vernon R. Tracy, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 10 ind. above ground, with brass cap mkd.												
	<p>COUNTY SURVEYORS OFFICE</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="padding: 0 5px;">T 21 S</td> <td></td> </tr> <tr> <td style="padding: 0 5px;">1/4</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;">R 4 W</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">1969</td> </tr> </table>		T 21 S		1/4	S 7	S 8		R 4 W				1969
	T 21 S												
1/4	S 7	S 8											
	R 4 W												
		1969											
	from which the remains of the original bearing trees												
	A decayed fir stump, 20 ins. diam., bears N. 79° W., 55 lks. dist., no marks visible.												
	and a bearing tree mkd. by Springer												
	A fir snag, 16 ins. diam., bears N. 50° E., 58 lks. dist., with scribe marks CS B visible on burned blaze.												