

County Surveyor's Record, Douglas County, Oregon

15029

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS													
25.95	Spur, slopes W.; desc. 145 ft. over NW. slope.												
39.80	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="font-family: cursive; font-size: small;"> <p>FIND OK 11-72 BY ROBERTS M 116-48</p> </div> <div style="text-align: center;"> <p>T 21 S R 4 W 1/4 S 6 S 5 1972</p> </div> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 4° E., 37 lks. dist., mkd. 1/4 S5 BT.</p> <p style="margin-left: 40px;">A fir, 28 ins. diam., bears N. 87° W., 44 lks. dist., mkd. 1/4 S6 BT.</p> <p>Descend 5 ft. over NW. slope.</p>												
40.90	Creek, 1 lk. wide, course S. 35° W.; asc. 210 ft. over S. slope.												
57.40	Ridge, bears N. 75° W. and S. 75° E.; desc. 110 ft. over NW. slope.												
78.61	<p>The cor. of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., firmly set, protruding 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>D.C.S.O.</p> <p>T 20 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 31</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 32</td> <td style="padding: 0 5px;">R</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">4</td> </tr> <tr> <td colspan="3"></td> <td style="padding: 0 5px;">W</td> </tr> </table> <p>T 21 S</p> <p>1968-366</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears N. 7° E., 47 lks. dist., with scribe marks 4 S BT visible on decayed blaze.</p> <p style="margin-left: 40px;">A fir snag, 13 ins. diam., bears S. 15° E., 58 lks. dist., with fragmentary scribe marks visible on opened blaze.</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears S. 43° W., 90 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Weyerhaeuser Timber Company, in 1958</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. 67° E., 136 1/2 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 28° E., 68 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 25 ins. diam., bears N. 7° W., 30 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by the County Surveyor, in 1968</p>	S 31		S 32	R	S 6		S 5	4				W
S 31		S 32	R										
S 6		S 5	4										
			W										