

# County Surveyor's Record, Douglas County, Oregon

15033

Dependent Resurvey, Portion of East Boundary,  
T. 25 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- A sawed fir stump, 54 ins. diam., bears N. 35° E., 79 lks. dist., no marks visible.
- A sawed fir stump, 40 ins. diam., bears S. 85° E., 25 lks. dist., with fragmentary scribe marks visible on decayed blaze.
- A sawed fir stump, 54 ins. diam., bears S. 37 1/4° W., 49 lks. dist., no marks visible on open blaze.
- A sawed fir stump, 58 ins. diam., bears N. 32 3/4° W., 50 lks. dist., no marks visible, and a nail with "W" embossed on head, driven into base.

and a bearing tree of which I have no record

- A sawed fir stump, 72 ins. diam., bears N. 87° E., 71 lks. dist., with a nail with "W" embossed on head, driven into base.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S	T 25 S
S 25	R 8 W
S 36	S 31
R 9 W	1972

Reset iron pipe alongside the iron post.

N.0° 19' E., on the E. bdy. of sec. 25, marking and blazing the true line.

Descend 35 ft. over NW. slope, through logged over area.

1.20 Creek, 1 lk. wide, course N. 70° W.; asc. 55 ft. over SW. slope.

3.97 Point for the closing cor. of secs. 30 and 31, T. 25 S., R.8 W., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S	T 25 S
R 9 W	S 30 CC
S 25	S 31
	R 8 W
	1972

from which bearing trees of which I have no record

- A sawed fir stump, 36 ins. diam., bears N. 54° E., 147 lks. dist., with a nail with "W" embossed on head, driven into base.

- A sawed fir stump, 66 ins. diam., bears S. 85° E., 178 lks. dist., with a nail with "W" embossed on head, driven into base.

No other suitable trees available within limits.

Ascend 30 ft. over S. slope.