

# County Surveyor's Record, Douglas County, Oregon

15034

Dependent Resurvey, Portion of East Boundary,  
T. 25 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
6.30	Gravelled road, 25 lks. wide, bears N. 70° W., curving to W. and S. 80° E., curving to E.
8.45	Top of ascent, slopes NW.; desc. 570 ft. over broken NW. slope.
13.10	Same gravelled road, 25 lks. wide, bears S. 10° W. and E.
28.00	Creek, 10 lks. wide, course N. 80° W.; asc. 250 ft. over S. slope.
29.40	Same gravelled road, 25 lks. wide, bears N. 80° W. and S. 80° E.
34.15	Spur, slopes S. 40° W.; asc. 50 ft. over SW. slope.
36.30	Ravine, drains. S. 40° W.; asc. 155 ft. over S. slope.
38.64	<p>The 1/4 sec. cor. of sec. 25 only, monumented with the original sandstone, 30 x 24 x 6 ins., mkd. 1/4 on W. face, firmly set, 18 ins. in the ground, alongside of which, an iron pipe, 1 in. diam., from which the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A sawed fir stump, 66 ins. diam., bears N. 54 3/4 ° E., 67 lks. dist., with healed blaze and a nail, with "W" embossed on the head, driven into base.</p> <p style="margin-left: 40px;">A sawed fir stump, 54 ins. diam., bears S. 51 1/2° W., 66 lks. dist., with healed blaze and a nail, with "W" embossed on the head, driven into base.</p> <p>At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="margin-left: 100px; border-left: 1px solid black; padding-left: 10px;"> <p style="margin: 0;">1/4 S 25</p> <p style="margin: 0;">T 25 S</p> <p style="margin: 0;">R 9 W</p> <p style="margin: 0;">1972</p> </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A dogwood, 6 ins. diam., bears S. 52° W., 50 lks. dist., mkd. 1/4 S25 BT.</p> <p style="margin-left: 40px;">Deposit corner stone and reset iron pipe alongside the iron post.</p> <hr style="width: 20%; margin-left: 40px;"/> <p>N. 1° 16' E., beginning new measurement.</p> <p>Ascend 15 ft. over S. slope.</p>
3.40	Top of ascent, slopes W.; desc. 10 ft. along W. slope.
5.30	Point for the 1/4 sec. cor. of sec. 30 only, T. 25 S., R. 8 W., hereinafter described.
	Descend 15 ft. along W. slope.
8.80	Ravine, drains. S. 40° W.; asc. 335 ft. over S. slope.
12.90	Gravelled road, 20 lks. wide, bears N. 70° W. and S. 70° E.