

# County Surveyor's Record, Douglas County, Oregon

15025

Dependent Resurvey, Portion of East Boundary,  
T. 25 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

- 15.00 Spur, slopes W.; desc. 190 ft. over NW. slope.
- 17.10 Same gravelled road, 20 lks. wide, bears N. 40° E. and S. 40° W.
- 20.65 Creek, 2 lks. wide, course N. 65° W.; asc. 5 ft. over SW. slope.
- 22.20 Top of ascent, slopes W.; desc. 50 ft. over NW. slope.
- 23.05 Ravine, drains. W.; asc. 55 ft. over SW. slope.
- 24.20 Spur, slopes W.; desc. 20 ft. over NW. slope.
- 25.25 Ravine, drains. S. 80° W.; asc. 170 ft. over broken SW. slope.
- 32.00 Spur, slopes N. 75° W.; desc. 145 ft. over broken NW. slope.

38.86 The cor. of secs. 24 and 25 only, monumented with the original sandstone, 24 x 12 x 4 ins., mkd. with 4 notches on the N. and 2 notches on the S. edges, loosely set, 5 ins. in the ground, from which the remains of the original bearing trees:

- A fir, 55 ins. diam., bears N. 64° E., 46 lks. dist., with healed blaze. (Record, 24 lks.)
  - A fir, 34 ins. diam., bears S. 81 3/4° E., 11 lks. dist., with healed blaze.
  - A fir, 74 ins. diam., bears S. 4 1/2° W., 89 1/2 lks. dist., with healed blaze. (Record, 46 lks.)
- and a bearing tree of which I have no record
- A fir, 40 ins. diam., bears N. 16 1/2° W., 14 lks. dist., with healed blaze and a nail, with "W" embossed on the head, driven into base.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S	T 25 S
S 24	R 8 W
S 25	S 30
R 9 W	
	1972

Deposit corner stone alongside the iron post.

Land, mountainous  
Soil, rocky clay loam.  
Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin, and yew; undergrowth, hazel, salal, fern, huckleberry, vine maple, and blackberry.

N. 1° 30' E., on the E. bdy. of sec. 24.

Descend 155 ft. over NW. slope. through dense timber and undergrowth.

- 1.80 Spur, slopes N. 35° W.; desc. 85 ft. over NE. slope.