

County Surveyor's Record, Douglas County, Oregon

15038

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS
39.92

The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 25 S
1/4 32-----33
R 8 W

from which bearing trees of which I have no record

A cedar, 24 ins. diam., bears N. 73 3/4° E., 44 lks. dist., with scribe marks 1/4 S BT visible on open blaze.

A cedar, 15 ins. diam., bears S. 83° W., 82 1/2 lks. dist., with scribe marks 1/4 S BT visible on open blaze.

N. 0° 31' W., beginning new measurement.

Ascend 410 ft. over SE. slope.

- 9.40 Spur, slopes N. 80° E.; desc. 330 ft. over NE. slope.
- 16.00 Creek, 3 lks. wide, course E.; asc. 240 ft. over SE. slope
- 24.95 Spur, slopes S. 75° E.; desc. 120 ft. over NE. slope.
- 29.15 Ravine, drains S. 75° E.; asc. 65 ft. over SE. slope.
- 30.60 Spur, slopes S. 70° E.; desc. 10 ft. over NE. slope.
- 31.80 Ravine, drains S 75° E.; asc. 100 ft. over SE. slope.
- 34.00 Spur, slopes N 70° E.; desc. 100 ft. over NE slope.
- 36.70 Ravine, drains N. 70° E.; asc. 50 ft. over SE. slope.
- 39.10 Top of ascent, slopes NE.; desc. 15 ft. over broken N. slope.
- 39.85 The original closing corner of secs. 29 and 32, on the W bdy. of sec. 33, perpetuated and recorded by Vernon Tracy, County Surveyor, in 1968, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, alongside of which the decayed remains of the original corner post, with brass cap mkd.

T 25 S
S 29
S 32 CC
R 8 W
1968

from which the remains of the original bearing trees

A fir snag, 36 ins. diam., bears S. 80° W., 8 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Tracy

A hemlock, 8 ins. diam., bears S. 54° W., 31 lks. dist., with scribe marks S32 CCCS visible on partially healed blaze.