

County Surveyor's Record, Douglas County, Oregon

15040

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

39.80

Point for the 1/4 sec. cor. of sec. only, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

Descend 175 ft. over NE. slope.

43.50

Creek, 7 lks. wide, course S. 65° E.; asc. 460 ft. over SW. slope.

53.50

Spur, slopes S. 35° E.; asc. 90 ft. over SE. slope.

59.00

Spur, slopes E.; desc. 445 ft. over NE. slope.

71.80

Arrow Creek, 3 lks. wide, course S. 60° E.; asc. 15 ft. over SW. slope.

76.72

Point for the closing cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 8 W

CC $\frac{S 20}{S 29}$ S 28

1972

from which

A hemlock, 11 ins. diam., bears S. 37 1/2° W., 183 lks. dist., mkd. T25S R8W S29 CC BT.

A hemlock, 17 ins. diam., bears N. 65 3/4° W., 245 lks. dist., mkd. T25S R8W S20 BT.

Ascend 15 ft. over SW. slope.

78.60

Top of ascent, slopes W.; desc. 10 ft. over N. slope.

79.50

Ravine, drains SW.; asc. 5 ft. over SW. slope.

79.60

The cor. of secs. 21 and 28 only, perpetuated and recorded by Vernon Tracy, County Surveyor, in 1968, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 25 S R 8 W

$\frac{S 21}{S 28}$

1968

from which the remains of the original bearing trees

A cedar snag, 48 ins. diam., bears S. 70° W., 28 lks. dist., no marks visible. (Record, 23 lks.)

and bearing trees mkd. by Wygant

A fir, 60 ins. diam., bears N. 85° E., 56 lks. dist., with healed blaze.

A cedar, 30 ins. diam., bears S. 0° 30' E., 84 lks. dist., with scribe mark W visible on partially healed blaze.