

County Surveyor's Record, Douglas County, Oregon

15013

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 25 S R 8 W
S 30 | S 29
S 31 | S 32
1972

from which new bearing trees

A hemlock, 8 ins. diam., bears N. 15 1/2° E., 53 lks.
dist., mkd. T25S R8W S29 BT.

A hemlock, 10 ins. diam., bears S. 9 1/2° E., 212 lks.
dist., mkd. T25S R8W S32 BT.

S. 89° 41' W., bet. sec. 30 and 31.

Ascend 270 ft. over broken E. slope, through heavy
timber and dense undergrowth.

3.90 Rock bluff, 25 ft. high, faces E.

5.20 Spur, slopes S. 35° E.; desc. 10 ft. over broken SW.
slope.

7.90 Ravine, drains S. 40° E.; asc. 190 ft. over SW. slope.

12.35 Ridge, bears N. 20° E. and S. 20° W.; also gravelled
road, 25 lks. wide, bears same as ridge; desc. 450 ft.
over NW. slope.

16.80 Bluff, 130 ft. high, faces W.

21.40 Spur, slopes N. 30° W.; desc. 65 ft. over NW. slope.

22.80 Ravine, drains N. 20° W.; asc. 25 ft. over SE. slope.

24.70 Spur, slopes N. 40° W.; desc. 215 ft. over broken N.
slope.

32.25 Creek, 2 lks. wide, course N. 35° W.; asc. 275 ft. over
SE. slope.

40.39 The 1/4 sec. cor. of secs. 30 and 31, determined at record
bearing and distance from the original bearing trees:

A hemlock, 28 ins., diam., bears N. 8° W., 35 lks.
dist., with fragmentary scribe marks visible on
partially healed blaze.

A hemlock, 18 ins. diam., bears S. 6° E., 26 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins.
in the ground, in a mound of stone, 2 ft. base, to top,
with brass cap mkd.

1/4 S 30
 S 31
T 25 S R 8 W
1972

N. 89° 58' W., beginning new measurement.

0.05 Ridge, bears N. and S.; desc. 425 ft. over SW. slope.