

County Surveyor's Record, Douglas County, Oregon

15015

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 50 ins. diam., bears S. $6\frac{1}{2}^\circ$ W., 22 lks.
dist., with healed blaze. (Record, S. 20° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

$\frac{1}{4}$
 S 30 | S 29
 T 25 S R 8 W
 1972

N. $0^\circ 03'$ E., beginning new measurement.

Ascend 5 ft. over SW. slope.

- 1.10 Top of ascent, slopes W.; desc. 100 ft. over NW. slope.
- 4.80 Creek, 5 lks. wide, course SW.; asc. 315 ft. over SE.
slope.
- 15.80 Spur, slopes N. 70° E.; desc. 70 ft. over NE. slope.
- 18.60 Creek, 1 lk. wide, course S. 65° E.; asc. 145 ft. over
SE. slope.
- 22.80 Spur, slopes S. 55° E.; desc. 30 ft. over NE. slope.
- 25.10 Ravine, drains. S. 65° E.; asc. 125 ft. over SE. slope.
- 28.60 Spur, slopes S. 70° E.; desc. 40 ft. over NE. slope.
- 30.45 Ravine, drains S. 75° E.; asc. 75 ft. over SE. slope.
- 33.70 Gravelled road, 25 lks. wide, bears N. 70° E., and
S. 70° W., also ridge, bears same as road; desc. 185 ft.
over NW. slope.
- 39.88 The cor. of secs. 19, 20, 29, and 30, perpetuated and
recorded by Vernon Tracy, County Surveyor, in 1968, monu-
mented with an iron post, 1 in. diam., firmly set, pro-
jecting 12 ins. above ground, with brass cap mkd.

T 25 S
 S 19 | S 20
 S 30 | S 29
 R 8 W
 1968

from which the remaining original bearing trees

A fir, 52 ins. diam., bears N. 15° E., $88\frac{1}{2}$ lks.
dist., with healed blaze and a galvanized nail,
With "W" embossed on the head, driven into base.
(Record, 99 lks.)

A fir, 70 ins. diam., bears S. 55° W., 94 lks.
dist., with healed blaze and a galvanized nail,
with "W" embossed on the head, driven into base.

A yew, 20 ins. diam., bears N. $16\frac{1}{2}^\circ$ W., 20 lks.
dist., with scribe marks T25S R8W S19 CS BT
visible on open blaze. This tree was rescribed
by Tracy.