

County Surveyor's Record, Douglas County, Oregon

15048

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- 22.25 Ravine, drains N. 15° E.; asc. 100 ft. over NE. slope.
- 24.65 Spur, slopes N. 20° E.; desc. 55 ft. over NW. slope.
- 26.35 Ravine, drains N. 35° E.; asc. 165 ft. over E. slope.
- 30.50 Ridge, bears N. 30° W. and S. 30° E.; desc. 145 ft. over W. slope.
- 35.05 Ravine, drains. S. 65° W.; desc. 20 ft. along S. slope.
- 39.66 The 1/4 sec. cor. of secs. 19 and 30, perpetuated and re-
corded by Vernon Tracy, County Surveyor, in 1968, monumented
with an iron post, 1 in. diam., firmly set, pro-
jecting 12 ins. above ground, with brass cap mkd.

T 25 S
1/4 $\frac{S 19}{S 30}$
R 8 W
1968

from which the original bearing trees

A fir, 48 ins. diam., bears N. 87° 36' E., 72 lks.
dist., with healed blaze.

A fir, 44 ins. diam., bears S. 3° 20' E., 72 lks.
dist., with fragmentary scribe marks visible
on partially healed blaze.

and bearing trees mkd. by Tracy

A fir, 10 ins. diam., bears N. 1° W., 14 lks.
dist., with scribe marks 1/4 S19 CS BT visible on
open blaze.

A hemlock, 9 ins. diam., bears S. 43 1/2° E., 32 1/2 lks.
dist., with scribe marks 1/4 S30 CS BT visible
on open blaze.

N. 89° 59' W., beginning new measurement.

Descend 125 ft. along S. slope.

- 7.25 Creek, 2 lks. wide, course N. 75° W.; desc. 20 ft. over
W. slope.
- 10.90 Rock bluff, 100 ft. high, faces W.; desc. 235 ft. over
W. slope.
- 14.30 Creek, 2 lks. wide, course N. 75° W.; desc. 265 ft.
over NW. slope.
- 20.27 Point for the W 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

W 1/16 $\frac{S 19}{S 30}$
1972

from which