

County Surveyor's Record, Douglas County, Oregon

19

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 40 ins. diam., bears N. 28° E., 36 lks.
dist., mkd. W 1/16 S19 BT.

A fir, 60 ins. diam., bears S. 33° W., 54 1/2 lks.
dist., mkd. W 1/16 S30 BT.

Descend 195 ft. over NW. slope.

25.20 Creek, 3 lks. wide, course N. 60° W.; asc. 35 ft. over
NE. slope.

29.15 Spur, slopes N. 50° W.; desc. 20 ft. over W. slope.

29.55 Creek, 1 lk. wide, course N. 20° W.; asc. 50 ft. over
E. slope.

31.20 Top of ascent, slopes N.; desc. 35 ft. along broken N.
slope.

36.60 Spur, slopes NW.; desc. 105 ft. over W. slope.

38.65 Creek, 3 lks. wide, course N. 30° W.; asc. 35 ft. over
NE. slope.

39.80 Intersect the E. bdy. of sec. 24, T. 25 S., R. 9 W.

True point for the closing cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 25 S	T 25 S	
	S 19	
R 9 W	S 30	CC
S 24	R 8 W	
		1972

from which

A hemlock, 22 ins. diam., bears N. 27 1/2° E., 150
lks. dist., mkd. T25S R8W S19 CC BT.

A hemlock, 25 ins. diam., bears S. 26° E., 19 lks.
dist., mkd. T25S R8W S30 BT.

From this point, the original closing cor. of secs. 19
and 30, bears N. 89° 59' W., 0.49 chs. dist., monumented
by person(s) unknown with an iron pipe, 1/2 in. diam.,
firmly set, projecting 6 ins. above ground, from which
the original bearing trees:

A fir, 40 ins. diam., bears N. 40° 30' E., 87 lks.
dist., with scribe marks S19 visible on partially
healed blaze.

A fir, 33 ins. diam., bears S. 57° 20' E., 53 lks.
dist., with scribe marks BT visible on partially
healed blaze.

From this same point, the cor. of secs. 24 and 25 only,
T. 25 S., R. 9 W., bears S. 1° 30' W., 6.43 chs. dist.,
hereinbefore described.

Land, mountainous.

soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, maple, alder, madrone,