

# County Surveyor's Record, Douglas County, Oregon

~~15049~~

**15050** Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

and Schinquapin; undergrowth, salal, hazel, fern, Oregon grape, and vine maple.

The point for the 1/4 sec. cor. of sec. 30 only, T. 25 S., R. 8 W., is at midpoint latitudinally on the W. bdy. of sec. 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 S 30  
T 25 S  
R 8 W  
1972

from which

A sawed fir stump, 36 ins. diam., bears S. 56 1/2° E., 54 1/2 lks. dist., mkd. 1/4 S30 BT.

A sawed fir stump, 42 ins. diam., bears S. 25° E., 82 lks. dist., mkd. 1/4 S30 BT.

From the cor. of secs. 17, 18, 19, and 20, determined from the remaining original bearing trees:

A fir, 45 ins. diam., bears N. 6° 30' E., 6 lks. dist., with healed blaze(Record, 43 lks.)

A hemlock, 20 ins. diam., bears S. 68° 30' W., 15 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A cedar, 30 ins. diam., bears N. 85° W., 34 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

At the corner point

Set on iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S, R 8 W  
S 18 | S 17  
S 19 | S 20  
1972

from which

A sandstone boulder, 4 x 4 x 6 ft. high, bears S. 24 1/2° E., 30 1/2 lks. dist., mkd. X B O on the NE. face.

N. 89° 41' E., bet. secs. 17 and 20.

Descend 255 ft. over NE. slope, through heavy timber and dense undergrowth.

5.80 Creek, 5 lks. wide, course N. 30° E.; asc. 180 ft. over NW. slope.

12.20 Spur, slopes N. 10° E.; desc. 200 ft. over NE. slope.

18.60 Creek, 15 lks. wide, course N. 15° W.; asc. 240 ft. over NW. slope.