

County Surveyor's Record, Douglas County, Oregon

15051

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- 26.30 Spur, slopes N. 10° E.; desc. 20 ft. over NE. slope.
- 27.50 Ravine, drains. N. 20° W.; asc. 55 ft. over NW. slope.
- 28.95 Spur, slopes N. 10° W.; desc. 25 ft. over NE. slope.
- 30.35 Ravine, drains. N. 15° W.; asc. 90 ft. over NW. slope.
- 32.25 Spur, slopes N. 10° E.; desc. 110 ft. over NE. slope.
- 35.40 Ravine, drains N. 5° W.; asc. 145 ft. over NW. slope.
- 38.30 Spur, slopes N. 35° W.; desc. 15 ft. over NE. slope.
- 39.57 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 $\frac{S\ 17}{S\ 20}$
T 25 S R 8 W
1972

from which

A hemlock, 6 ins. diam., bears N. 55° W., 24 1/2 lks. dist., mkd. 1/4 S17 BT.

A hemlock, 13 ins. diam., bears S. 21° W., 26 lks. dist., mkd. 1/4 S20 BT.

Descend 15 ft. over NE. slope.

- 40.20 Head of ravine, drains N. 10° E.; asc. 60 ft. over N. slope.
- 44.20 Top of ascent, slopes N.; desc. 155 ft. over NE. slope.
- 49.50 Creek, 10 lks. wide, course NW.; asc. 375 ft. over W. slope.
- 62.80 Top of ascent, slopes E.; desc. 70 ft. over SE. slope.
- 68.90 Creek, 4 lks. wide, course SW.; asc. 110 ft. over NW. slope.
- 71.10 Dirt road, 20 lks. wide, in curve, bears N. 35° E. and S. 20° W.
- 71.90 Ridge, bears N. 25° E. and S. 25° W.; desc. 575 ft. over broken NE. slope.
- 84.84 Intersect the W. bdy. of sec. 21.

True point for the closing cor. of secs. 17 and 20.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S
CC $\frac{S\ 17}{S\ 20}$ S 21
R 8 W
1972