

# County Surveyor's Record, Douglas County, Oregon

15056

T. 22 S., R. 5 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the east boundary and subdivisional lines, township 22 south, range 5 west, Willamette Meridian, Oregon.

The history of surveys in this township that pertain to this resurvey, is as follows:

The east boundary and a portion of the subdivisional lines were surveyed by Harvey Gordon and Charles T. Gardner, in 1855.

The Matthew Lyons Donation Land Claim No. 43, was surveyed by Dennis Hathorn, in 1856.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were re-established and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding, or crossing, public lands were blazed.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions, dated May 22, 1973, for Group Number 812, Oregon.

The directions of the lines were determined by deflection angles turned from azimuths obtained by direct solar observations.

The geographic position of the corner of sections 25, 30, 31 and 36, on the east boundary of the township, as scaled from the Anlauf, Oregon, quadrangle map, prepared by the United States Geological Survey, in 1954, is as follows:

Latitude  $43^{\circ} 37.2' N.$  Longitude  $123^{\circ} 13.6' W.$

The mean magnetic declination is  $20^{\circ} 15' E.$

---

Dependent Resurvey of a Portion of the East Boundary,  
T. 22 S., R. 5 W., Willamette Meridian, Oregon

---

(Restoring the 1855 survey by Harvey Gordon  
and Charles T. Gardner, Deputy Surveyors)

Beginning at the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S

1/4

R5W S 25 | S 30 R4W

1963

from which the remains of the original bearing trees