

County Surveyor's Record, Douglas County, Oregon

15058

Dependent Resurvey of a Portion of the East Boundary,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

and a bearing tree mkd. by Godfrey

A fir, 9 ins. diam., bears S. 6 1/2° W., 62 lks.
dist., with healed blaze.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, alder, maple, madrone, yew,
and chinquapin; undergrowth, vine maple, hazel, fern,
salal ocean spray, blackberry, and poison oak.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Harvey Gordon
and Charles T. Gardner, Deputy Surveyors)

From the cor. of secs. 25, 30 31 and 36, on the E.
bdy. of the Tp., perpetuated by James W. Byron, Deputy
County Surveyor, in 1959, monumented with an iron post,
2 1/4 ins. diam., firmly set, protruding 8 ins. above
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE			
T 22 S			
	S 25	S 30	
R5W	S 36	S 31	R4W
1959			

from which the remains of the original bearing trees

A sawed fir stump, 30 ins. diam., bears S. 37° E.,
39 1/2 lks. dist., with healed blaze. (Record,
33 lks.)

A sawed fir stump, 40 ins. diam., bears S. 16° W.,
46 lks. dist., with scribe mark 6 visible on
opened blaze.

A root hole, bears N. 52° W., 41 lks. dist., with
a down fir alongside, 44 ins. diam., no marks
visible.

and bearing trees mkd. by Byron

A fir, 63 ins. diam., bears N. 15° E., 197 lks.
dist., with healed blaze.

A cedar, 25 ins. diam., bears S. 13 1/2° E., 139 lks.
dist., with healed blaze.

A fir, 13 ins. diam., bears S. 78° W., 59 1/2 lks.
dist., with healed blaze.

and a new bearing tree

A fir, 6 ins. diam., bears N. 41° W., 56 1/2 lks.
dist., mkd. T22S R5W S25 BT.

The corner is located at the intersection of wire
fences extending N., E., and W.