

# County Surveyor's Record, Douglas County, Oregon

15059

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

N. 89° 59' W., bet. secs. 25 and 36, marking and blazing the true line.

Ascend 305 ft. over NE. slope, through heavy timber and dense undergrowth.

12.40 Ridge, bears N. 30° W. and S. 30° E.; desc. 280 ft. over SW. slope.

20.275 Point for the E 1/16 sec. cor. of secs. 25 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16  $\frac{S\ 25}{S\ 36}$   
1973

from which

A fir, 26 ins. diam., bears N. 17 1/2° E., 45 lks. dist., mkd. E 1/16 S25 BT.

A fir, 19 ins. diam., bears S. 64° E., 13 1/2 lks. dist., mkd. E 1/16 S36 BT.

Descend 195 ft. over SW. slope.

26.15 Creek, 1 lk. wide, course S.; asc. 350 ft. over SE. slope.

37.00 Spur, slopes S. 35° E.; desc. 40 ft. over SW. slope.

40.55 The 1/4 sec. cor. of secs. 25 and 36, determined at record bearing, from the original bearing trees:

A cedar, 34 ins. diam., bears N. 42° W., 52 lks. dist., with healed blaze.

A fir, 54 ins. diam., bears S. 57 1/2° E., 79 lks. dist., with scribe marks 1/4 S visible on weathered bark blaze. (Record, 72 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FO. EVIDENCE  
UNDER SLIDE  
10/92 K. HOFFME  
M 116-2*

1/4  $\frac{S\ 25}{S\ 36}$   
T 22 S R 5 W  
1973

*REFERENCED OUT FOR  
ROAD CONSTRUCTION - BY  
W. HAINES 12/4/80 - SEE  
CS 59/50*

S. 89° 47' W., beginning new measurement.

Descend 15 ft. over SW. slope.

.50 Ravine, drains S. 15° E.; asc. 235 ft. over SE. slope.

12.30 Ridge, bears N. 35° E. and S. 35° W.; desc. 140 ft. over NW. slope.

19.40 Bottom of descent, slopes N.; asc. 85 ft. over broken NE. slope.

26.60 Spur, slopes SE.; desc. 140 ft. over broken SW. slope.