

# County Surveyor's Record, Douglas County, Oregon

15060

~~15060~~

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

34.00

Bottom of descent, slopes S.; asc. 220 ft. over SE. slope.

39.45

The cor. of secs. 25, 26, 35 and 36, determined at record bearing and distance, from the remains of the original bearing trees:

A fir, 35 ins. diam., bears S. 29 1/2° E., 82 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.

A fir, 55 ins. diam., bears S. 17° W., 155 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FND OK 10/92  
K. HOFFME M116-2*

T 22 S R 5 W  
S 26 | S 25  
S 35 | S 36  
1973

from which new bearing trees

A fir, 21 ins. diam., bears N. 24° E., 81 1/2 lks. dist., mkd. T22S R5W S25 BT.

A fir, 23 ins. diam., bears N. 25° W., 45 1/2 lks. dist., mkd. T22S R5W S26 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, madrone, maple, yew chinquapin, and alder; undergrowth, vine maple, hazel, fern, salal, ocean spray and poison oak.

From the 1/4 sec. cor. of secs. 25 and 26, determined at record bearing and distance, from the remains of the original bearing tree:

A fir, 48 ins. diam., bears N. 22° E., 85 lks. dist., with scribe mark B visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4  
S 26 | S 25  
T 22 S R 5 W  
1973

from which a new bearing tree

A fir, 8 ins. diam., bears S. 54° W., 43 lks. dist., mkd. 1/4 S26 BT.

N. 0° 38' E., bet. secs. 25 and 26.

Descend 15 ft. over NE. slope, through scattering timber and dense undergrowth.

1.00

Ravine, drains N. 30° W.; asc. 40 ft. over SW. slope.