

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

- 2.70 Spur, slopes W.; desc. 105 ft. over NW. slope.
- 12.80 Ravine, drains N. 70° W.; asc. 175 ft. over SW. slope.
- 19.86 Point for the N 1/16 sec. cor. of secs. 25 and 26.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- N 1/16
S 26 | S 25
1973
- from which
- A fir, 16 ins. diam., bears N. 62° E., 13 1/2 lks. dist., mkd. N. 1/16 S25 BT.
- A fir, 10 ins. diam., bears N. 38 1/4° W., 7 lks. dist., mkd. N 1/16 S26 BT.
- Ascend 20 ft. over SW. slope.
- 20.90 Spur, slopes W.; desc. 200 ft. over N. slope.
- 25.40 Ravine, drains N. 70° W.; asc. 75 ft. over SW. slope.
- 28.70 Spur, slopes W.; desc. 25 ft. over NW. slope.
- 31.45 Ravine, drains S. 40° W.; asc. 160 ft. over SE. slope.
- 37.30 Spur, slopes S. 50° W.; desc. 40 ft. over NW. slope.
- 39.72 The cor. of secs. 23, 24, 25 and 26, determined at record bearing and distance, from the remains of the original bearing trees:
- A sawed fir stump, 23 ins. diam., bears N. 63° E., 35 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.
- A sawed fir stump, 50 ins. diam., bears N. 22° W., 29 lks. dist., no marks visible on opened and decayed blaze.
- At the corner point
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 22 S R 5 W
S 23 | S 24
S 26 | S 25
1973
- from which new bearing trees
- A fir, 6 ins. diam., bears N. 63 1/4° E., 56 lks. dist., mkd. T22S R5W S24 BT.
- A fir, 5 ins. diam., bears S. 14° E., 21 1/2 lks. dist., mkd. T22S R5W S26 BT.
- A fir, 5 ins. diam., bears S. 1 1/4° W., 84 1/2 lks. dist., mkd. T22S R5W S26 BT.
- A fir, 41 ins. diam., bears N. 35 3/4° W., 32 lks. dist., mkd. T22S R5W S23 BT.