

County Surveyor's Record, Douglas County, Oregon

~~15062~~
15062

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, alder, maple, madrone
and chinquapin; undergrowth, vine maple, hazel, salal,
fern, ocean spray and arrowwood.

From the cor. of secs. 19, 24, 25 and 30, on the E.
bdy. of the Tp.

N. 89° 31' W., bet. secs. 24 and 25.

Ascend 65 ft. over E. slope, through scattering timber
and dense undergrowth.

- 2.50 Spur, slopes N.; desc. 20 ft. over NW. slope.
- 6.05 Private road, gravelled, 15 lks. wide, bears NE. and SW.
- 6.40 Ravine, drains N. 30° E.; asc. 125 ft. over broken NE.
slope.
- 14.90 Leave timber and undergrowth, edge bears N. and S.;
enter open field.
- 19.975 Point for the E 1/16 sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 24}{S\ 25}$
1973

from which

A fir, 13 ins. diam., bears N. 31° W., 44 lks.
dist., mkd. E 1/16 S24 BT.

A fir, 9 ins. diam., bears S. 30° E., 109 1/2 lks.
dist., mkd. E 1/16 S25 BT.

Ascend 95 ft. over NE. slope.

- 27.50 Spur, slopes S.; desc. 125 ft. over W. slope.
- 28.90 Leave open field, enter heavy timber and moderate
undergrowth, edge bears N. and S.
- 30.75 Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.
- 32.60 Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.
- 32.90 Creek, 2 lks. wide, course N. 20° W.; asc. 120 ft.
over broken E. slope.
- 39.95 Point for the 1/4 sec. cor. of secs. 24 and 25, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

1/4 $\frac{S\ 24}{S\ 25}$

T 22 S R 5 W
1973