

County Surveyor's Record, Douglas County, Oregon

15083

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 13 ins. diam., bears N. 66 1/2° E., 81 1/2 lks. dist., mkd. 1/4 S24 BT.

A fir, 9 ins. diam., bears S. 85° E., 93 1/2 lks. dist., mkd 1/4 S25 BT.

Ascend 70 ft. over broken E. slope.

44.70 Spur, slopes N. 50° E.; desc. 50 ft. over NW. slope.

47.55 Bottom of descent, slopes N.; asc. 250 ft. over NE. slope.

59.75 Wire fence, bears N. 10° E. and S. 10° W.

65.15 Ridge, bears N. and S.; desc. 205 ft. over NW slope.

71.00 Ravine, drains S. 60° W.; asc. 60 ft. over SE. slope.

77.15 Spur, slopes SW.; desc. 80 ft. over W. slope.

79.90 The cor. of secs. 23, 24, 25 and 26.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, cedar, madrone, maple, chinquapin, and yew; undergrowth, vine maple, hazel, salal, fern, ocean spray and poison oak.

N. 0° 03' E., bet. secs. 23 and 24.

Descend 20 ft. over NW slope, through scattering timber and dense undergrowth.

1.00 Ravine, drains S. 50° W.; asc. 90 ft. over SW. slope.

5.05 Spur, slopes S. 50° W.; desc. 75 ft. over NW slope.

9.45 Ravine, drains S. 50° W.; asc. 160 ft. over SE. slope.

15.15 Ridge, bears NW. and SE.; desc. 20 ft. over NE slope.

19.935 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

FDOK PER PEEL
2/23/88 M 105-69

S 1/16
S 23 | S 24
1973

from which

A fir, 8 ins. diam., bears East, 49 lks. dist., mkd. S 1/16 S24 BT.

A fir, 10 ins. diam., bears N. 82° W., 103 lks. dist., mkd. S 1/16 S23 BT.

Descend 180 ft. over NE. slope.

39.87 Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.