

County Surveyor's Record, Douglas County, Oregon

15064

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FD OK PER PEEL
2/23/88 M 105-69*

1/4
S 23 | S 24
T 22 S R 5 W
1973

from which

A fir, 10 ins. diam., bears S. 47° E., 36 lks. dist., mkd. 1/4 S24 BT.

A fir, 10 ins. diam., bears N. 33° W., 66 1/2 lks. dist., mkd. 1/4 S23 BT.

Descend 495 ft. over NE. slope.

58.10 Creek, 5 lks. wide, course N. 55° W.; asc. 115 ft. over SW. slope.

66.45 Spur, slopes W.; desc. 80 ft. over broken NW. slope.

79.74 The cor. of secs. 13, 14, 23 and 24, perpetuated by B. H. McGillicuddy, Deputy County Surveyor, in 1955, from original evidence no longer in existence, subsequently perpetuated by Bruce R. Rodgers, Deputy County Surveyor, in 1965, monumented with an iron pipe, 1 in. diam., firmly set, protruding 8 ins. above ground, from which bearing trees mkd. by Rodgers:

A fir, 16 ins. diam., bears S. 43° E., 26 1/2 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. 25° W., 50 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 33° W., 27 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FD OK PER PEEL
2/23/88 M 105-69*

T 22 S R 5 W
S 14 | S 13
S 23 | S 24
1973

from which a new bearing tree

A fir, 10 ins. diam., bears N. 62° E., 46 1/2 lks. dist., mkd. T22S R5W S13 BT.

Deposit iron pipe alongside iron post.

The corner is located at the intersection of wire fences extending N., S., E. and W.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, madrone, maple, yew and chinquapin; undergrowth, vine maple, hazel, salal, fern, blackberry and ocean spray.

From the cor. of secs. 23, 24, 25 and 26.