

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 5 W., Willamette Meridian, Oregon

15065

CHAINS

N. 89° 03' W., bet. secs. 23 and 26.

Descend 40 ft. over NW. slope, through scattering timber and dense undergrowth.

- .95 Ravine, drains S. 50° W.; asc. 20 ft. over SE. slope.
- 4.75 Spur, slopes S. 50° W.; desc. 300 ft. over SW. slope.
- 15.05 Ravine, drains NW.; asc. 15 ft. over SE. slope.
- 17.40 Spur, slopes N. 30° E.; desc. 45 ft. over NW. slope.
- 19.25 Creek, in Dodge Canyon, course N. 60° E.; asc. 15 ft. over SE. slope.
- 19.655 Point for the E. 1/16 sec. cor. of secs. 23 and 26.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

FD OK PER. PEEL
2/23/88 M105-69

$$\begin{array}{r} S\ 23 \\ E\ 1/16\ S\ 26 \\ 1973 \end{array}$$

from which

A hemlock, 14 ins. diam., bears N. 63 1/2° E., 58 1/2 lks. dist., mkd. E 1/16 S23 BT.

A fir, 26 ins. diam., bears S. 5° W., 100 lks. dist., mkd. E 1/16 S26 BT.

Ascend 250 ft. over SE. slope.

- 30.25 Spur, slopes N. 20° E.; desc. 105 ft. over W. slope.
- 33.40 Ravine, drains N. 20° E.; asc. 120 ft. over NE. slope.
- 35.20 Dirt road, 10 lks. wide, bears N. and S.
- 37.90 Spur, slopes N. 20° E.; desc. 20 ft. over NW. slope.

- 39.31 The 1/4 sec. cor. of secs. 23 and 26, perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron pipe, 1 in. diam., firmly set, protruding 4 ins. above ground, from which the remains of the original bearing trees:

FD OK PER. PEEL
2/23/88 M105-69

A root Hole, bears N. 2° E., 79 lks. dist., with a down fir alongside, 46 ins. diam., no marks visible.

A sawed and decayed fir stump, 36 ins. diam., bears S. 42° W., 44 lks dist., with scribe marks 4S visible on remains of open blaze.

and bearing trees mkd. by Godfrey

A fir, 14 ins. diam., bears N. 30° W., 37 lks. dist., with healed blaze.

A fir, 23 ins. diam., bears S. 2° E., 135 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 lks. in the ground, with brass cap mkd.