

County Surveyor's Record, Douglas County, Oregon

15073

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 14 ins. diam., bears N. 25 3/4° E., 162 lks. dist., with healed double blaze.

N. 0° 11' W., beginning new measurement.

Ascend 110 ft. over SW. slope, across logged area, along line bearing N.

9.00 Spur, slopes S. 10° W.; desc. 10 ft. along broken E. slope.

18.90 Edge of timber bears NW., enter moderate timber and undergrowth.

19.825 Point for the N 1/16 sec. cor. of secs. 10 and 11.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 10 | S 11
1969

from which

A fir, 8 ins. diam., bears S. 17 1/2° E., 15 lks. dist., mkd. N 1/16 S11 BT.

A fir, 10 ins. diam., bears N. 72 3/4° W., 8 1/2 lks. dist., mkd. N 1/16 S10 BT.

Continue descending 10 ft. along broken E. slope.

24.30 Intersection of wire fences, bears S. and W.

25.70 Ravine, drains S. 65° E.; asc. 410 ft. over S. slope.

39.65 The cor. of secs. 2, 3, 10 and 11, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

*FD. OK
3/91 M III-70*

COUNTY SURVEYOR'S OFFICE
T 28 S
S 3 | S 2
S 10 | S 11
R 8 W
1957

from which the remains of the original bearing tree

A root hole, bears N. 81° E., 39 lks. dist., with a down fir alongside, 28 ins. diam., with scribe marks BT visible in negative on overgrowth.

and bearing trees marked by Byron

A cedar, 10 ins. diam., bears N. 43° E., 79 lks. dist., with healed double blaze.

A cedar, 13 ins. diam., bears S. 46° E., 38 lks. dist., with healed double blaze.

and bearing trees of which I have no record

A fir, 45 ins. diam., bears N. 5° E., 84 lks. dist., with scribe marks T28S R8W S2 BT visible on bark.