

County Surveyor's Record, Douglas County, Oregon

15074

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 34 ins. diam., bears S. 21° E., 69 lks.
dist., with scribe marks T28S R8W BT visible on
bark.

A cedar, 15 ins. diam., bears S. 78° W., 32 lks.
dist., with scribe marks 28 BT visible on
partially healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, myrtle, oak, alder,
and chinquapin; undergrowth, vine maple, Oregon grape,
salal, fern, poison oak, rhododendron, blackberry,
huckleberry, salmonberry, and elderberry.

From the 1/4 sec. cor. of secs. 27 and 28, perpetuated
and recorded by Howard W. Johnstone, for Roseburg
Lumber Co., in 1962, subsequently perpetuated by John
M. Powell, Deputy County Surveyor, in 1966, monumented
with an iron post, 1 1/2 ins. diam., firmly set, protruding
8 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

T28S
1/4 S 28 S 27
R8W
1966

from which the remaining original bearing tree

A cedar, 40 ins. diam., bears S. 1° E., 24 lks.
dist., with scribe marks 4S visible on opened
blaze.

and a bearing tree marked by Johnstone

A fir, 9 ins. diam., bears S. 48° W., 16 lks.
dist., with healed blaze.

N. 0° 01' W., bet. secs. 27 and 28.

Ascend 225 ft. over SW. slope, through moderate timber
and light undergrowth.

19.50 Top of ascent, slopes W.; desc. 440 ft. over NW. slope.

37.55 Creek, 3 lks. wide, course N. 45° W.; asc. 50 ft. over
SW. slope.

39.74 The original cor. of secs. 21, 22, 27 and 28 determined
from the remains of the original bearing trees:

A fir stump, 48 ins. diam., bears N. 20° E.,
79 lks. dist., with scribe marks BT visible
on opened blaze.

A fir, 24 ins. diam., bears S. 15° E., 73 lks.
dist., with healed blaze. (Record, 69 lks.)

A madrone, 18 ins. diam., bears N. 75° W., 45 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.