

County Surveyor's Record, Douglas County, Oregon

15076

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

20.085

Point for the E 1/16 sec. cor. of secs. 22 and 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

E 1/16 $\frac{S\ 22}{S\ 27}$
1973

from which

A fir, 8 ins. diam., bears N. 40° E., 27 lks. dist., mkd. E. 1/16 S22 BT.

A fir, 13 ins. diam., bears S. 41° W., 84 lks. dist., mkd. E. 1/16 S27 BT.

Descend 20 ft. over SW. slope.

20.70

Ravine, drains S. 25° E.; asc. 140 ft. over SE. slope.

24.55

Spur, slopes S.; desc. 235 ft. over SW. slope.

35.60

Creek, 2 lks. wide, course S.; asc. 20 ft. over broken SE. slope.

40.17

Point for the 1/4 sec. cor. secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R8W
1/4 $\frac{S\ 22}{S\ 27}$
1973

from which

A fir, 11 ins. diam., bears N. 5 1/2° E., 29 lks. dist., mkd. 1/4 S22 BT.

A fir, 8 ins. diam., bears S. 38° W., 21 lks. dist., mkd. 1/4 S27 BT.

Ascend 35 ft. over SE. slope.

44.15

Spur, slopes S.; desc. 5 ft. over SW. slope.

45.55

Little Muley Creek, 2 lks. wide, course S. 40° E.; asc. 105 ft. over E. slope.

53.25

Spur, slopes N.; desc. 10 ft. over W. slope.

55.30

Little Muley Creek, 1 lk. wide, course N. 65° E.; asc. 130 ft. over E. slope.

65.95

Top of ascent, slopes N.; desc. 330 ft. over W. slope.

80.34

The cor. of secs. 21, 22, 27 and 28.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, alder, madrone, maple and