

County Surveyor's Record, Douglas County, Oregon

15078

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- A fir, 17 ins. diam., bears N. 73° E., 87 1/2 lks. dist., with healed double blaze.
 - A hemlock, 26 ins. diam., bears S. 2 1/2° E., 60 lks. dist., with healed double blaze.
 - A fir, 30 ins. diam., bears S. 45° W., 62 lks. dist., with healed blaze.
 - A sawed white fir stump, 15 ins. diam., bears N. 86° W., 64 lks. dist., no marks visible.
 - A fir snag, 14 ins. diam., bears N. 83 1/2° W., 71 lks. dist., with healed double blaze.
- and a bearing tree marked by Roseberry, in 1969
- A fir, 20 ins. diam., bears N. 57° W., 141 lks. dist., with scribe marks T28S R8W S16 BT visible on partially healed blaze.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, alder, maple, madrone and chinquapin; undergrowth, vine maple, hazel, fern, salal, and poison oak.

N. 0° 04' W., bet. secs. 15 and 16.

Descend 160 ft. over NW. slope, through moderate timber and undergrowth.

- 8.10 Dirt road, 12 lks. wide, bears NE. and SW.
 - 8.30 Creek, 10 lks. wide, course E.; asc. 505 ft. over SE. slope.
 - 33.15 Spur, slopes N. 65° E.; desc. 240 ft. over NW. slope.
 - 40.11 Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T28S R8W
1/4
S 16 | S 15
1969

FD 02
BC 4 BT
11/22/69

from which

- A fir, 10 ins. diam., bears N. 32 1/2° E., 40 lks. dist., mkd. 1/4 S15 BT.
- A chinquapin, 12 ins. diam., bears N. 15 3/4° W., 47 lks. dist., mkd. 1/4 S16 BT.

Continue descending 240 ft. over NW. slope.

- 47.90 Tenmile Creek, 12 lks. wide, course S. 80° E.; asc. 380 ft. over SW. slope.
- 48.80 Coos Bay Wagon Road, asphaltic surfaced, 30 lks. wide, bears N. 75° W., and S. 75° E.