

# County Surveyor's Record, Douglas County, Oregon

15081

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

- 44.90 Creek, 1 lk. wide, course S. 35° E.; asc. 150 ft. over E. slope.
- 46.20 Spur, slopes S.; desc. 40 ft. over SW. slope.
- 48.90 Creek, 4 lks. wide, course SE.; asc. 240 ft. over E. slope.
- 64.65 Spur, slopes S. 30° W.; desc. 115 ft. over W. slope.
- 79.76 The cor. of secs. 9, 10, 15 and 16.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, hemlock, cedar, madrone, myrtle, oak, alder, and chinquapin; undergrowth, vine maple, Oregon grape, salal, fern, poison oak, rhododendron, blackberry, huckleberry, salmonberry and elderberry.

N. 1° 29' E., bet. secs. 9 and 10.

Ascend 615 ft. over S. slope, through heavy timber and light undergrowth, along wire fence extending N. and S.

- 13.05 Leave wire fence, bears NE. and S.
- 24.10 Spur, slopes S. 35° E.; desc. 145 ft. over NE. slope.
- 36.20 Creek, 2 lks. wide, course SE.; asc. 80 ft. over broken SE. slope.
- 39.20 Creek, 2 lks. wide, course S. 15° W.; asc. 20 ft. over SE. slope.
- 40.12 Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 28 S R 8 W  
1/4  
S 9 | S 10  
1969

from which

A fir, 10 ins. diam., bears N. 28° E., 71 lks. dist., mkd. 1/4 S10 BT.

A fir, 8 ins. diam., bears N. 44 1/2° W., 118 lks. dist., mkd 1/4 S9 BT.

Corner falls in dirt road, 15 lks. wide, bears E. and W., and 3 lks. W. of creek, course S. 15° W.

Continue ascending 690 ft. over broken SE. slope.

- 60.18 Point for the N 1/16 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

N 1/16  
S 9 | S 10  
1969