

County Surveyor's Record, Douglas County, Oregon

15082

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 36 ins. diam., bears N. 67 3/4° E., 83 lks.
dist., mkd. N 1/6 S10 BT.

A fir, 37 ins. diam., bears N. 37 1/4° W., 68 lks.
dist., mkd. N 1/16 S9 BT.

Continue ascending 235 ft. over broken SE. slope.

65.50 Spur, slopes S. 80° W.; desc. 210 ft. over NW. slope.

80.24 The cor. of secs. 3, 4, 9 and 10, perpetuated and
recorded by James W. Byron, Deputy County Surveyor, in
1961, monumented with an iron pipe, 1 1/2 ins. diam.,
firmly set, protruding 6 ins. above ground, with brass
cap mkd.

COUNTY SURVEYOR'S OFFICE

T 28 S
S 4 | S 3
S 9 | S 10
R 8 W
1961

from which the remains of the original bearing trees

A fir stump, 32 ins. diam., bears N. 53° E., 70
lks. dist., with scribe marks 28S R8W S3 visible
on bark. (Record, 60 lks.)

A fir stump, 45 ins. diam., bears S. 4 1/4° E., 22
lks. dist., no marks visible.

and trees marked by Byron

A hemlock, 14 ins. diam., bears N. 57° E., 96 lks.
dist., with scribe marks 8 R8 visible on
partially healed blaze.

A fir stump, 12 ins. diam., bears S. 15 1/2° E., 28
lks. dist., with scribe marks S R8W visible on
partially healed blaze.

A hemlock, 13 ins. diam., bears S. 44° W., 96 lks.
dist., with scribe marks S R8W S9 BT visible on
partially healed blaze.

A hemlock, 29 ins. diam., bears N. 84° W., 48 lks.
dist., with scribe marks T28S R8W S4 CS BT
visible on open blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, myrtle, oak, alder
and chinquapin; undergrowth, vine maple, Oregon grape,
salal, fern, poison oak, rhododendron, blackberry,
huckleberry, salmonberry and elderberry.

From the cor. of secs. 2, 3, 10 and 11.

S. 89° 42' W., bet. secs. 3 and 10.

Ascend 490 ft. over broken SE. slope, through heavy
timber and light undergrowth.