

County Surveyor's Record, Douglas County, Oregon

15084

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T28S R8W

1/4 $\frac{S\ 21}{S\ 28}$
1973

from which

A fir, 11 ins. diam., bears N. 17° W., 43 lks.
dist., mkd. 1/4 S21 BT.

A fir, 13 ins. diam., bears S. 37 1/2° E., 82 lks.
dist., mkd. 1/4 S28 BT.

Ascend 285 ft. over broken NE. slope.

60.48 Point for the W 1/16 sec. cor. of secs. 21 and 28.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

W 1/16 $\frac{S\ 21}{S\ 28}$
1973

from which

A fir, 24 ins. diam., bears N. 68° W., 98 lks.
dist., mkd. W 1/16 S21 BT.

A fir, 8 ins. diam., bears S. 22° E., 19 lks.
dist., mkd. W 1/16 S28 BT.

Ascend 470 ft. over broken NE. slope.

80.64 The cor. of secs. 20, 21, 28 and 29, perpetuated by
James W. Byron, Deputy County Surveyor, in 1957, mon-
umented with an iron post, 1 1/2 ins. diam., firmly set,
protruding 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE

T28S R8W
 $\frac{20|21}{29|28}$
1957

from which the remaining original bearing trees

A fir, 50 ins. diam., bears N. 10° E., 27 lks.
dist., with healed blaze.

A fir, 42 ins. diam., bears S. 30° E., 38 lks.
dist., with scribe marks BT visible on opened
blaze.

and bearing trees marked by Byron

A fir, 14 ins. diam., bears S. 47° E., 63 lks.
dist., with healed double blaze.

A chinquapin, 8 ins. diam., bears S. 34 1/2° W.,
37 lks. dist., with healed double blaze.

A maple, 12 ins. diam., bears N. 16° W., 20 lks.
dist., with healed double blaze.

Land, mountainous.