

# County Surveyor's Record, Douglas County, Oregon

15086

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 8 W., Willamette, Meridian, Oregon

CHAINS

From the cor. of secs. 19, 20, 29 and 30, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYOR'S OFFICE  
T28S  
S 19 | S 20  
S 30 | S 29  
R8W  
1963

from which the remains of the original bearing trees

A sawed fir stump, 44 ins. diam., bears N. 65° E., 32 lks. dist., no marks visible.

A root hole, bears S. 55° E., 11 lks. dist.

A fir snag, 32 ins. diam., bears S. 60° W., 18 lks. dist., no marks visible.

A fir stump, 44 ins. diam., bears N. 30° W., 16 lks. dist., no marks visible.

and bearing trees marked by Byron

A fir, 7 ins. diam., bears N. 35° E., 45 lks. dist., with healed double blaze.

A cedar, 12 ins. diam., bears S. 2° E., 59 lks. dist., with healed double blaze.

A hemlock, 12 ins. diam., bears S. 77° W., 85 lks. dist., with healed double blaze.

A hemlock, 13 ins. diam., bears N. 69° W., 46 lks. dist., with healed double blaze.

N. 0° 28' W., bet. secs. 19 and 20.

Descend 60 ft. over NW. slope, through heavy timber and light undergrowth.

1.00 Creek, 3 lks. wide, course N. 60° W.; asc. 430 ft. over SW. slope.

25.50 Spur ridge, bears S. 80° E.; desc. 60 ft. over NW. slope.

30.20 Ravine, drains S. 70° W.; asc. 115 ft. over SW. slope.

40.69 Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 8 W  
1/4  
S 19 | S 20  
1972

from which

*FD B.C.F. 875 OK  
7/16/85  
PER P. GAINOR L.S. 1988  
C.S. 6/3/22*