

# County Surveyor's Record, Douglas County, Oregon

15088

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

and bearing trees marked by Byron

A cedar, 25 ins. diam., bears N. 35° E., 59 lks. dist., with healed blaze.

A white fir snag, 16 ins. diam., bears S. 45° E., 17 lks. dist., with scribe marks T28S R8W CS S21 BT visible on open blaze.

and new bearing trees

A fir, 11 ins. diam., bears S. 73° E., 24 lks. dist., mkd. T28S R8W S17 BT.

A fir, 12 ins. diam., bears N. 50° W., 61 lks. dist., mkd. T28S R8W S17 BT.

N. 89° 48' W., bet. secs. 17 and 20.

Ascend 455 ft. over E. slope, through heavy timber and light undergrowth.

13.00 Coos Bay Wagon Road, paved, 40 lks. wide, bears N. 15° E., and S. 15° W.

18.75 Coos Bay Wagon Road, paved, 40 lks. wide, bears S. 25° E., and N. 25° W.

28.55 Coos Bay Wagon Road, paved, 40 lks. wide, bears N. 40° E., and S. 30° W.

30.75 Burnt Ridge Road, dirt, 20 lks. wide, bears N. 45° E., and S. 45° W.

40.26 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 8 W  
1/4  $\frac{S 17}{S 20}$   
1972

*FD. B.C. OK  
7/19/85  
(FD BT's To Be Monitored)  
PER R. GEISLER L.S. 1988  
C.S. 63/22*

from which

A fir, 12 ins. diam., bears North, 57 lks. dist., mkd. 1/4 S17 BT.

A fir, 10 ins. diam., bears S. 9° W., 50 lks. dist., mkd. 1/4 S20 BT.

Ascend 1 ft. over E. slope.

42.75 Spur, slopes S.; desc. 217 ft. over broken SW. slope.

69.75 Coos Bay Wagon Road, paved, 40 lks. wide, bears S. 45° E., and N. 45° W.

70.05 East Fork of Coquille River, 10 lks. wide, course N. 45° W.; asc. 365 ft. over NE. slope.

80.52 The cor. of secs. 17, 18, 19 and 20.

Land, mountainous.  
Soil, rocky clay loam.