

County Surveyor's Record, Douglas County, Oregon

15089

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 28 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Timber, fir, hemlock, cedar, alder, maple and madrone;
undergrowth, vine maple, hazel, salal, poison oak and
fern.

S. 89° 40' W., bet. secs. 18 and 19.

Ascend 85 ft. over NE. slope through heavy timber and
moderate undergrowth.

- 6.20 Spur, slopes N.; desc. 235 ft. over NW. slope.
 - 18.30 Leave timber, edge bears N. and S.
 - 19.50 Paved road, 30 lks. wide, bears N. and S.; asc. 360 ft.
over NE. slope.
 - 37.80 Enter timber, edge bears N. and S.
 - 40.06 Point for the 1/4 sec. cor. of secs. 18 and 19, at pro-
portionate distance; there is no remaining evidence of
the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 28 S R 8 W
1/4 $\frac{S 18}{S 19}$
1972

from which

A fir, 18 ins. diam., bears N. 15° W., 54 lks.
dist., mkd. 1/4 S18 BT.

A fir, 24 ins. diam., bears S. 57° W., 68 lks.
dist., mkd. 1/4 S19 BT.

Ascend 15 ft. over NE. slope.

- 43.25 Spur, slopes N.; desc. 80 ft. over NW. slope.
- 48.50 Creek, 2 lks. wide, course N. 20° W.; asc. 75 ft. over
broken SW. slope.
- 71.55 Ridge, bears S. 10° E., and N. 10° W.; desc. 110 ft.
over SW. slope.
- 72.20 Dirt road, 20 lks. wide, bears S. 20° E. and North.
- 80.42 The cor. of secs. 13, 18, 19 and 24, on the West
boundary of the Tp., perpetuated and recorded by John L.
Safstrom, RLS. No. 477, in 1961, monumented with an
iron pipe, 1 1/2 ins. diam., firmly set, protruding 4 ins.
above ground, from which the remaining original bearing
tree:
 - A fir, 45 ins. diam., bears S. 60° E., 36 lks.
dist., with scribe marks 8 BT visible on
weathered bark blaze.

and bearing trees marked by Safstrom

 - A yew, 5 ins. diam., bears N. 71 1/2° E., 19 lks.
dist., with scribe marks S8 BT visible on open
blaze.
 - A hemlock, 18 ins. diam., bears S. 21° W., 24 lks.
dist., with scribe marks S24 BT visible on open